

PRODUCT DATA SHEET VSSC204DD



Rapid Self-Seal 204x60mm Duct to Duct Connector







MANUFACTURER: VERPLAS LTD

PART NUMBER: VSSC204DD

> SIZE: 204x60mm

VERPLAS SYSTEM 204 FOR USE WITH:

BOX QUANTITY: 56

INDIVIDUAL WEIGHT: 209a

> COLOUR White

MIN OPERATING TEMP -15°C

MAX OPERATING TEMP +60°C

SPECIFICATION DETAILS

The VSSC204DD 204x60mm Rectangular Self-Seal Coupling Duct to Duct is manufactured from (white) High Impact Polystyrene and has a minimum free area of 9,750mm2. The VSC204DD incorporates a gasket to reduce air leakage to an absolute minimum in connections between System 204 ducting.


The VSSC204DD is fully compliant with SAP Appendix Q Product Characteristics Database recommendations for duct sizes used with both extract and Mechanical Heat Recovery Systems.

VSSC204DD is manufactured in compliance with Domestic Plastic Ductwork Specification DW/154 and does meet UL94HB flammability standard.

VSSC204DD has been designed for use with Verplas System 204.

AIRFLOW	RESISTANCE
8 I/s	0.13 pa
13 l/s	0.30 Pa
21 l/s	0.60 Pa
30 l/s	1.17 Pa
60 I/s	3.30 Pa
120 l/s	10.42 Pa

Pressure Loss **Pascals** (Pa)



Associated Ancillaries

VSSC5630 VKC5629 204X60mm Rapid 204x60mm VSSC204DF Self-Seal T-Piece 204x60mm Rapid Self-Seal 2m Flat Channel **Duct to Fitting Connector**



Scan Here to find out how quick it is to install







