



PRODUCT DATA SHEET

VKC289

COWLED OUTLET C/W NON-RETURN FLAP ROUND SPIGOT



W RAL9010

B RAL8017

BE RAL1001

T RAL2001

SPECIFICATION DETAILS

The VKC289 125mm diameter Cowled Outlet with Non-Return Flap Round Spigot is manufactured from High Impact Polypropylene and has a minimum free area of 6,560mm². It has a male spigot for connection inside of the System 125 duct.

The VKC289 is designed for installation on exposed external walls where wind or back pressure against the ventilation unit are present. The cowled outlet is designed to shield the duct from the wind and deflect the air away. The non-return flap acts as an additional measure to prevent airflow returning through the duct. As the fan operates the flap lifts to allow the exhaust air to disperse into the atmosphere. VKC289 is designed for exhaust air only.

VKC289 is manufactured in compliance with Domestic Plastic Ductwork Specification DW/154 and does meet UL94HB flammability standard.

VKC289 has been designed for use with Verplas System 125 Round.

MAX/MIN OPERATING TEMPERATURES

+ 60°C to - 15°C

Manufacturer:

Verplas Ltd

Part Number:

VKC289

Size:

125mm Diameter

For use with:

Verplas System 125

Box quantity:

15


Individual Weight:

145g

Colour:

White, Brown, Beige & Terracotta

PERFORMANCE CURVE



AIRFLOW

RESISTANCE

8 l/s

3.60 pa

13 l/s

5.00 pa

21 l/s

8.00 pa

30 l/s

19.83 pa

60 l/s

74.99 pa

120 l/s

283.64 pa

Associated Ancillaries

125mm 2m Round Pipe



VKC2692

125mm Round Ceiling Vent Diffuser



VKC356F

125mm Round Wall Plate



VKC618

125mm Pipe to Pipe Self-Seal Coupling



VSSC125PP

125mm Pipe to Fitting Self-Seal Coupling



VSSC125PF