

# PRODUCT DATA SHEET

## INTUMESCENT SLIM FIRE SLEEVES

### FIRE SOLUTIONS RANGE



#### FEATURES AND BENEFITS

CE Marked

Tested to BSEN 1366-3: 2009 and classified according to EN 13501-2: 2007 +A1: 2009

Tested with Uncapped/Uncapped (U/U) duct configurations as required for ventilation ducts.

Up to 2 hour fire rating

Very slim-line (saves ceiling space)

Suitable for masonry walls or plasterboard partitions

Suitable for insulated and non insulated partitions

Can be retrofitted

No mechanical fixings required

Robust galvanised steel shell

Performance unaffected by weathering (Type X Durability)



#### SPECIFICATION DETAILS

QRS CE Marked Intumescent Slim Fire Sleeves prevent the spread of fire where plastic pipes penetrate fire compartment walls. They are specifically designed to be slim for applications where there is limited space around the duct.

The QRS CE Marked Intumescent Slim Fire Sleeves consist of a flexible galvanized steel shell containing graphite based intumescent material.

They are manufactured to suit flat ducts; 110x54mm, 204x60mm and 220x90mm. Please note QRS110/54SS is available on request.

PRODUCT CODE	FIRE RATING	DUCT SIZE	SPACE NEEDED AROUND DUCT TO FIT SLEEVE	RECOMMENDED APPROX APERTURE	QRS LENGTH
QRS204/60SS	90 MINUTES	204 X 60MM	6.5MM	217 X 73MM	140MM
QRS220/90SS	60 MINUTES	220 X 90MM	12MM	244 X 114MM	140MM
QRS110/54SS (On Request)	120 MINUTES	110 X 54MM	7MM	124 X 68MM	140MM

#### Associated Ancillaries



 [Sales@Verplas.co.uk](mailto:Sales@Verplas.co.uk)  
 [www.Verplas.co.uk](http://www.Verplas.co.uk)  
 +44 (0) 1202 825898

View the Full Range

