



# PRODUCT DATA SHEET

## SST-125-1M-IND

Rapid Self-Seal Thermal 125mmØ 1m Length with Duct to Duct Fitting



MANUFACTURER:	VERPLAS LTD
PART NUMBER:	SST-125-1M-IND
SIZE:	125mmØ
FOR USE WITH:	VERPLAS THERMAL 125
BOX QUANTITY:	6
INDIVIDUAL WEIGHT:	341g
COLOUR	Grey
MIN OPERATING TEMP	-15°C
MAX OPERATING TEMP	+60°C
THERMAL RESISTANCE	0.666 m <sup>2</sup> K/W
THERMAL CONDUCTIVITY	0.03 W/mK

### SPECIFICATION DETAILS

The Verplas Self-Seal Thermal SST-125-1M-IND 1m length of insulated duct is manufactured from graphite impregnated expanded polystyrene (EPS) with a density of 25kg/m<sup>3</sup> and provides a free area of 12,273 mm<sup>2</sup>. The SST-125-1M-IND is supplied with a single Duct to Duct connector to fit into the next straight length of duct. The open end of the duct allows a push-fit over a 125mm Fan Spigot or it can be cut to length to insert a Duct to Fitting Connector to push, click and lock into the female coupling housed in every Fitting. The Duct to Duct connections and Duct to Fitting Connectors are manufactured from prime quality High Impact Polystyrene.

The EPS material is fully tested to meet the thermal conductivity requirements of BASF-EN13163 to assist with the prevention of condensation and is flame retardant to DIN 4102-B1.

The patented push, click and lock mechanism provides a low leakage solution which exceeds the requirements set out in DW/143 Class A leakage test and DW/154 ductwork standards.


The Self-Seal Thermal is compliant with the requirements outlined in the Energy performance characteristics database for use in SAP with MVHR and MEV supply and extract ventilation systems.

### AIRFLOW RESISTANCE

8 l/s	0.10 pa
13 l/s	0.20 pa
21 l/s	0.40 pa
30 l/s	0.80 pa
60 l/s	3.10 pa
120 l/s	11.60 pa

### PERFORMANCE CURVE

Pressure  
Loss  
Pascals  
(Pa)



AIRFLOW RATE  
(L/S)

### Associated Ancillaries

- SST-125-45B-IND  
125mmØ 45° Round Rapid  
Thermal Self-Seal Bend
- SST-125-2M-IND  
125mmØ Rapid  
Thermal Self-Seal 2m Pipe
- SST-125-90B-IND  
125mmØ 90° Rapid  
Self-Seal Thermal Bend



Scan Here  
to find out  
how quick  
it is to install

