
PRODUCT DATA SHEET VSSC351



Rapid Self-Seal 125mmØ 45° Round Bend







MANUFACTURER: VERPLAS LTD

PART NUMBER: VSSC351

> SIZE: 125mmØ

VERPLAS SYSTEM 125 FOR USE WITH:

BOX QUANTITY: 24

INDIVIDUAL WEIGHT: 270a

> COLOUR White

MIN OPERATING TEMP -15°C

MAX OPERATING TEMP +60°C

SPECIFICATION DETAILS

The VSSC351 125mmØ Rapid Self-Seal 45° Round Bend is manufactured from (white) high impact polystyrene and has a free area of 11,461mm². The Rapid Self-Seal 45° Round Bend incorporates a gasket to reduce air leakage to an absolute minimum between System 125mm ducting.

The VSSC351 is fully compliant with SAP Appendix Q Product Characteristics Database recommendations for duct sizes used with both extract and Mechanical Heat Recovery Systems.


The VSSC351 is manufactured in compliance with Domestic Plastic Ductwork Specification DW/154 and does meet UL94HB flammability standard.

The VSSC351 is designed for use with the Verplas System 125mm.

AIRFLOW	RESISTANCE
8 l/s	0.24 pa
13 l/s	0.60 pa
21 l/s	1.54 pa
30 l/s	3.12 pa
60 I/s	12.36 pa

Pressure Loss **Pascals** (Pa)

PERFORMANCE CURVE



AIRFLOW RATE (L/S)

Associated Ancillaries













